

STUMPJUMPER FSR EXPERT CARBON EVO 650b



HYP GRN/BLK

SPECIFICHE TECNICHE (Le specifiche possono cambiare senza preavviso)

- Telaio FSR in fibra di carbonio FACT 9m, geometria EVO, carro posteriore in lega M5 con battuta mozzo 142+. Escursione 150mm, cuscinetti sigillati sui punti di infulcro, movimento centrale PF30. Grafiche asimmetriche.
- Ammortizzatore Fox Float CTD Factory con valvola Boost, rivestimento Kashima e funzione di AUTOSAG. Tre regolazioni sulla compressione: Salita, Trail e Discesa.
- Nuova forcella RockShox Pike RC con 150mm di escursione, insieme al manubrio low-rise 750mm per una guida fluida e precisa.
- Ruote All Mountain Roval Traverse 142+ con meccanismo e raggi DT Swiss, asse passante anteriore 15mm.
- Pneumatico anteriore Butcher e Purgatory sul posteriore, entrambi nella versione Control 2,3" 2Bliss Ready.
- Trasmissione SRAM X01 a 11 velocità con guarnitura dedicata SRAM S2200 in fibra di carbonio. Cassetta SRAM X0 10-42.
- Nuovo reggisella telescopico Specialized Command Post IR con regolazione su 3 posizioni con comando remoto e passaggio guaina interno.

TELAIO	FACT 9m carbon front triangle, EVO geometry, FACT IS construction, M5 alloy rear triangle, tapered headtube, carbon PF30 BB, ISCG '05, internal Command Post IR routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm travel
AMMORTIZ. POST	Custom FOX Float CTD Factory w/ AUTOSAG and Boost Valve, Kashima coating, Climb, Trail, Descend settings and reb adj., 195x51mm
FORCELLA	RockShox Pike, Solo Air spring, tapered alloy steerer, comp, and reb adj., 15mm thru-axle, 150mm travel
SERIE STERZO	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
ATTACCO MANUBRIO	Specialized XC, 3D forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
MANUBRIO	Specialized All-Mountain, low-rise, 7050 alloy, 750mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
MANOPOLE	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular, Others: XL thickness
FRENO ANTERIORE	Shimano XT M-785, hydraulic disc, S/M: 180mm rotor, Others: 200mm
FRENO POSTERIORE	Shimano XT M-785, hydraulic disc, S/M: 160mm rotor, Others: 180mm
LEVE FRENO	Shimano XT M-785, hydraulic disc
CAMBIO POSTERIORE	SRAM X01 Type 2, 11-speed, mid cage
COMANDI	SRAM X01, 11-speed, trigger
PACCO PIGNONI	SRAM X01 XG-1195, 11-speed, 10-42
CATENA	SRAM X1, 11-speed w/ power link
GUARNITURA	Custom SRAM S-2200 Carbon, PF30 spindle, S: 170mm, Others: 175mm
INGRANAGGI	34T
MOVIMENTO CENTR.	SRAM PF30, OS press-in bearings, sealed cartridge
CERCHI	Roval Traverse 650b, alloy disc, 28mm wide, 27/32h
MOZZO ANTERIORE	Roval Traverse SL, 15mm thru-axle end caps, 27h
MOZZO POSTERIORE	Roval Traverse 142+, XX1 driver body, 12mm thru-axle, 32h
RAGGI	DT Swiss Super Comp, 2,0/1.65/1.8 stainless
PNEUMATICO ANT.	Specialized Butcher Control, 2Bliss Ready, 650bx2.3", foldable aramid bead, 60TPI
PNEUMATICO POST.	Specialized Purgatory Control, 2Bliss Ready, 650bx2.3", foldable aramid bead, 60 TPI
CAMERE D'ARIA	Ultralight presta valve
SELLA	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
REGGISELLA	Specialized Command Post IR, 3-position, internally routed adjustable height w/ air spring, remote operated, single bolt head, 30.9mm, S: 100mm travel, Others: 125mm
COLLARINO SELLA	Specialized 7050 hard anodized alloy, single bolt, 34.9mm

ART. NR.	DESCRIZIONE	COLORE	MIS.
93314-3402	EXPERT CARBON EVO 650B HYP GRN/BLK		S
93314-3403			M
93314-3404			L
93314-3405			XL

STUMPJUMPER FSR COMP EVO 650b



CYAN/FLTH WHT/BLK

- Telaio FSR in lega M5, escursione 150mm con geometria EVO. Tubo sterzo conico, carro compatibile 142+, movimento centrale PF30 e cuscinetti sigillati sui punti di infulcro. Nuove grafiche asimmetriche.
- Ammortizzatore Fox Float CTD Evolution con AUTOSAG e regolazione su 3 posizioni in compressione: Salita, Trail e Discesa.
- Forcella RockShox Revelation RC3, corsa 150mm con tubo sterzo conico, asse passante 15mm e tre regolazioni in compressione.
- Cerchi Roval con mozzo posteriore Specialized Hi Lo 142x12mm e perno passante 15mm sull'anteriore.
- Guarnitura dedicata 2x10 SRAM S-1250 All Mountain, PF30.
- Manubrio Specialized All-Mountain low-rise, larghezza 750mm.
- Pneumatico anteriore Butcher e Purgatory sul posteriore, entrambi nella versione Control 2,3" 2Bliss Ready.
- Cambio posteriore SRAM X9, trasmissione 2x10 con cassetta 11-36.
- Reggisella telescopico Specialized BlackLite con regolazione su 3 posizioni con comando remoto.

SPECIFICHE TECNICHE (Le specifiche possono cambiare senza preavviso)

TELAIO	M5 hydroformed tubing, EVO geometry, tapered headtube, PF30 BB, ISCG '05, Command Post BlackLite routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm travel
AMMORTIZ. POST	Custom FOX Float CTD Evolution w/ AUTOSAG, Climb, Trail, Descend settings and reb adj., 195x51mm
FORCELLA	Custom RockShox Revelation RC3, 3P damper, tapered alloy steerer, 3-position compression and reb adj., 15mm thru-axle, 150mm travel
SERIE STERZO	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
ATTACCO MANUBRIO	Specialized XC, 3D forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
MANUBRIO	Specialized All-Mountain, low-rise, 7050 alloy, 750mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
MANOPOLE	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular, Others: XL thickness
FRENO ANTERIORE	Shimano Deore M-615, hydraulic disc, Ice Tech pads, S/M: 180mm rotor, Others: 200mm
FRENO POSTERIORE	Shimano Deore M-615, hydraulic disc, Ice Tech pads, S/M: 160mm rotor, Others: 180mm
LEVE FRENO	Shimano Deore M-615, hydraulic disc
DERAGLIATORE ANT.	SRAM X7, 10-speed, S3 direct mount for DMD, bottom pull
CAMBIO POSTERIORE	SRAM X9 Type 2, 10-speed, mid cage
COMANDI	SRAM X7, 10-speed, w/ MatchMaker clamp
PACCO PIGNONI	SRAM PG-1030, 10-speed, 11-36
CATENA	PC1051, 10-speed, w/ power link, nickel finish
GUARNITURA	Custom SRAM S-1250, 7050 alloy arms, 10-speed AM double, PF30 spindle, S: 170mm, Others: 175mm
INGRANAGGI	36/24, w/ alloy guard
MOVIMENTO CENTR.	SRAM PF30, OS press-in bearings, sealed cartridge
CERCHI	Roval 650b, alloy disc, 24mm wide, 32h
MOZZO ANTERIORE	Specialized Hi Lo disc, sealed cartridge bearings, 15mm thru-axle, 32h
MOZZO POSTERIORE	Specialized Hi Lo disc, four-sealed cartridge bearings, 12mm thru-axle, 32h
RAGGI	DT Swiss Industry, 2.0 stainless
PNEUMATICO ANT.	Specialized Butcher Control, 2Bliss Ready, 650bx2.3", foldable aramid bead, 60TPI
PNEUMATICO POST.	Specialized Purgatory Control, 2Bliss Ready, 650bx2.3", foldable aramid bead, 60 TPI
CAMERA D'ARIA	Ultralight presta valve
SELLA	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
REGGISELLA	Command Post BlackLite, new "alien head" design, 30.9mm height adjustable single bolt, w/ remote adjust lever. S: 100mm travel, Others: 125mm
COLLARINO SELLA	Forged alloy, single bolt, 31.8mm

ART. NR	DESCRIZIONE	COLORE	MIS
97514-5002	COMP EVO 650B	CYAN/FLTH WHT/BLK	S
97514-5003			M
97514-5004			L
97514-5005			XL